

Q

Search UniFi products

Dome & Turret

>

AI Dome

Datasheet

In The Box

Marketing Images

Installation Guide



^

Overview

Dimensions	Ø118 x 90.8 mm (Ø4.6 x 5.5")
IR Night Vision	40 m (131 ft)
Face Recognition	✓
License Plate Recognition	✓
Smart Detections (People, Vehicles, Animals)	✓
Resolution	4K
Field of View	H: 109.9°, V: 56.7°, D: 134.1°
Audio	Microphone
Weatherproofing	IP66
Tamper Resistance	IK10
Mounting	Arm, ceiling , pendant, wall mount, junction box

^

Performance



Networking Interface	GbE RJ45 port
Video	
Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR
Max. Frame Rate	30 FPS
Resolution	8MP 3840 x 2160 (16:9)
Optics	
Sensor	1/1.8" 8MP
Lens	Fixed focal length
Night Mode	Built-in IR LED illumination and IR cut filter
^ Hardware	
Max. Power Consumption	10W
Supported Voltage Range	42.5—57V DC
Power Method	PoE
Processor	Quad-core Arm® Cortex®-A53 based chip
Weight	700 g (1.5 lb)
Enclosure Material	Aluminum alloy, polycarbonate
Mount Material	Surface mount: polycarbonate
Expansion Slot	MicroSD Card
Button	(1) Factory-reset
Cable	
Cable Connector Type	RJ45
Cable Diameter	4.5 mm (0.2")
Cable Length	30 cm (1 ft)
Jacket Material	Thermoplastic elastomer
Jacket Enclosure Dimensions	Ø20 x 70.6 mm (0.8 x 2.8")
Jacket Enclosure Material	Thermoplastic elastomer, polycarbonate, silicone rubber



Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity	0 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC

Stay in Touch

Email 

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.

