

Search UniFi products

Dome & Turret

>


G5 Turret Ultra

Datasheet

In The Box

Marketing Images

Installation Guide



^

Overview

Dimensions	Ø90 x 71.2 mm (Ø3.5 x 2.8")
IR Night Vision	30 m (98 ft)
Smart Detections (People, Vehicles, Animals)	✓
Resolution	2K
Field of View	H: 102.4°, V: 54.9°, D: 120.6°
Audio	Microphone
Weatherproofing	IP66
Tamper Resistance	IK04
Mounting	Wall, ceiling mount (Included) Junction box, arm mount (Optional)

^

Performance

Networking Interface	10/100 MbE RJ45 port
----------------------	----------------------

Video

Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay
Max. Frame Rate	30 FPS
Resolution	4MP 2688 x 1512 (16:9)

Optics

Sensor	1/2.4" CMOS
Lens	Fixed focal length
Night Mode	Built-in IR LED illumination and IR cut filter

^ Hardware

Max. Power Consumption	4W
Supported Voltage Range	37—57V DC
Power Method	PoE
Processor	Dual-core Arm® Cortex®-A7 based chip
Weight	330 g (11.6 oz)
Enclosure Material	Aluminum alloy, UV-stabilized polycarbonate
Mount Material	Polycarbonate
Button	(1) Factory-reset

Cable

Cable Connector Type	RJ45
Cable Diameter	5 mm (0.2")
Cable Length	30 cm (1 ft)
Jacket Material	Polycarbonate
Jacket Enclosure Dimensions	Ø20 x 70.6 mm (0.8 x 2.8")
Jacket Enclosure Material	Thermoplastic elastomer, polycarbonate, silicone rubber
Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity	0 to 90% noncondensing

NDAA Compliant



Certifications

CE, FCC, IC

Stay in Touch

Email



Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.