UISP UniFi **Branding**

Q Search UniFi products

Switching WiFi Camera Security Door Access Integrations Advanced Hosting

Special Devices > Al Port

Datasheet	In The Box	Marketing Images	Installation Guide	
	2 3	. tuntesing integer		



*PoE+ input required for PoE output (12.95W), PoE++ input required for PoE+ output (25.5W).

**Rack mount sold separately,

*** SD card support coming soon.

∧ Overview

Without mount: 150 x 64 x 38.4 mm (5.9 x 2.5 x 1.5") **Dimensions** With mount: 152.7 x 69 x 47.8 mm (6 x 2.7 x 1.9")

Max. camera resolution: Width: 3840 pixels

Height: 2160 pixels

Networking Interface (1) GbE RJ45 port

∧ Hardware

Resolution

PoE

Power Method PoE+ input required for PoE output (12.95W)

PoE++ input required for PoE+ output (25.5W)

Pole Mount Diameter >45 mm (1.8") on pipe outer diameter

Weight Without mount: 258.3 g (9.1 oz)

With mount: 294 g (10.4 oz)

Enclosure Material Polycarbonate

Button Factory-reset

Ambient Operating Temperature -20 to 40° C (-4 to 104° F)

Ambient Operating Humidity 20 to 90% noncondensing

Certifications FCC, IC, CE

∧ Software

Application Requirements

Web Application UniFi Protect: Version 5.1 and later

Mobile App UniFi Protect iOS™ and Android™

Stay in Touch



Terms of Service | Privacy Policy | Legal | Cookies Settings

© 2025 Ubiquiti, Inc. All rights reserved.