

Q

Search UniFi products

Switching

WiFi

Camera Security

Door Access

Integrations

Advanced Hosting

PTZ > G5 PTZ

Datasheet

In The Box

Marketing Images

Installation Guide



Overview

Dimensions

Without mount: Ø90 x 152.5 mm
(Ø3.5 x 6")

With mount: 90 x 94 x 179.5 mm
(3.5 x 3.7 x 7")

IR Night Vision

20 m (65 ft)

Zoom Mode

2x Optical

Smart Detections (People, Vehicles, Animals)

✓

Resolution

2K

Field of View

Wide: H: 99.7°, V: 51.9°, D: 121°
Tele: H: 45.5°, V: 25.4°, D: 52.4°

Pan-Tilt Range

Pan: 350°
Tilt: 100°

Audio

Microphone

Weatherproofing

IP66

Tamper Resistance	IK04
Mounting	Wall mount, pole mount (Included) Conduit adapter, surface, in-ceiling, pendant, corner mount (Optional)
^ Performance	
Networking Interface	10/100 MbE RJ45 port
Video	
Max. Frame Rate	30 FPS
Resolution	4MP 2688 x 1512 (16:9)
Optics	
Sensor	5MP 1/2.7" CMOS
Lens	F 3.42-6.85 mm; f/1.85-f/2.4
Night Mode	Built-in IR & white LED illumination with IR cut filter
^ Hardware	
Max. Power Consumption	14W
Supported Voltage Range	37—57V DC
Power Method	PoE+
Pole Mount Diameter	1.5-2" (38-50 mm)
Weight	Without mount: 580 g (1.3 lb) With mount: 650 g (1.4 lb)
Enclosure Material	Aluminum alloy, polycarbonate
Mount Material	Wall mount: polycarbonate Pole mount: aluminum alloy
Button	(1) Factory-reset
Ambient Operating Temperature	-30 to 45° C (-22 to 113° F)
Ambient Operating Humidity	0 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC

Stay in Touch

Email



Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.