

Search UniFi products

For Door Access > [Access Button](#)

Datasheet

In The Box

Marketing Images

Installation Guide

^ Mechanical

Dimensions	137 x 88 x 38.1 mm (5.4 x 3.5 x 1.5")
Weight	180 g (6.3 oz)
Enclosure Material	Polycarbonate
Mount Material	Polycarbonate, SGCC steel
Available Colors	Black, white
Indoor and Outdoor Use	Indoor only

^ Hardware

Mechanical Life	1,000,000 clicks
Power Method	UniFi Access Hubs UL 294 Power-limited Class 2 PSU UL 60950-1/62368-1 LPS/PS2 PSU
Contact Type	(1) Normal open
Contact Rating	30V DC, 2A

UL 294 Level	Destructive attack: Level I Line security: Level I Endurance: Level I Standby power: Level I
UL 294 Statement	Compliance with IEEE 802.3 (at or af) specifications was not verified as part of UL 294. The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.
CAN/ULC-60839-11-1 Grade	Grade assignment: 1
Document number, and issue date and/or revision level	UA-Button, V01
Ambient Operating Temperature	0 to 40° C (32 to 104° F)
Ambient Storage Temperature	-40 to 70° C (-40 to 158° F)
Ambient Operating Humidity	5 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, UL 294, CAN/ULC-60839-11-1
Certification	CE, UL 294, CAN/ULC-60839-11-1

Stay in Touch

